

PRODUCT SPEC SHEET

GYROGUIDE GWD40™

Gyro While Drilling

GENERAL SPECS

Probe Length	18.56 – 23.78 ft	5.66 - 7.25 m
Probe OD (Standard Probe)	1.875 in	47.625 mm
Probe Weight	165 lbs	75 kg
Probe Pressure Rating	20,000 psi	151.7 MPa
Probe Temperature Range (standard probe)	32° - 300°F	0- 150°C
Vibration	8g RMS (all axis)	
Survey Accuracy *	Wellbore Dependent	
Host Collar Size #	4.75 in – 9.5 in	


* ISCWSA / SPE WTS compliant error ellipse reports are available upon request for specific well profiles

Available collar sizes dependent on MWD / Directional provider.

SENSOR SPECS

Sensor Type	Stationary north finding spinning mass rate gyroscope	
Running Mode	Gyrocompass, Continuous Toolface	
Measurement	Range	Accuracy
Inclination	0 - 40°	± 0.05°
Azimuth	0 - 360°	± 0.5°
Tool Face	0 - 360°	± 0.1°
Gravity Tool Face	-180° - 180°	± 1°

Specifications are subject to change based on well profile. Contact your Gyrodata representative for details. Updated April 2019. Copyright ©2019 Gyrodata, Inc. Patent: www.gyrodata.com/patents



Gyrodata's gyro while drilling GyroGuide GWD40 service provides advanced collision avoidance and real-time knowledge of wellbore position, enhancing performance and safety in magnetic environments. This modular gyro while drilling tool is combined with a host measurement while drilling (MWD) & Telemetry system, and provides rate-gyroscopic surveys in vertical or lower inclination applications.

DESIGN + PERFORMANCE

- Rate gyro accuracy assures precise wellbore guidance for collision avoidance
- Provides continuous inclination and tool face from vertical while sliding, and full surveys on demand
- Unaffected by magnetic interference, the sensors can run closer to the bit in the MWD string by eliminating the need for non-magnetic spacing collars for the gyro sensor
- Eliminates the need to use wireline gyros to orient or steer the drilling assemblies, which saves considerable rig time and provides for safer operations
- The tool can be run with the most commonly available MWD systems

MARKET + APPLICATIONS

- Vertical & Low Inclination Drilling
- Batch Well Setting
- Directional Drilling
- RSS Drilling
- Mining - Freeze Ring
- Areas of Magnetic Interference
- Multi-Well Pad Drilling
- Collision Avoidance
- Offshore & Riser Less Drilling
- Casing While Drilling
- Onshore Drilling